


六方阳螺纹接头



NPT 阳螺纹

P-NPT 尺寸	Px-NPT 尺寸	基本订购号	尺寸, mm					压力额定值 psig (bar)	
			L	F	B	Bx	E	316 不锈钢, 碳钢	黄铜
1/16	1/16	S-N1	25.6	7.9	9.7	9.7	3.0	11000 (757)	5500 (378)
1/8	1/16	S-N2N1	25.6	11.1	9.7	9.7	3.0	11000 (757)	5500 (378)
1/8	1/8	S-N2	25.6	11.1	9.7	9.7	4.8	10000 (689)	5000 (344)
1/4	1/16	S-N4N1	31.0	14.3	14.2	9.7	3.0	11000 (757)	5500 (378)
1/4	1/8	S-N4N2	31.0	14.3	14.2	9.7	4.8	10000 (689)	5000 (344)
1/4	1/4	S-N4	35.6	14.3	14.2	14.2	7.1	8000 (551)	4000 (275)
3/8	1/16	S-N6N1	31.8	17.5	14.2	9.7	3.0	11000 (757)	5500 (378)
3/8	1/8	S-N6N2	31.8	17.5	14.2	9.7	4.8	10000 (689)	5000 (344)
3/8	1/4	S-N6N4	36.3	17.5	14.2	14.2	7.1	8000 (551)	4000 (275)
3/8	3/8	S-N6	36.3	17.5	14.2	14.2	9.7	7800 (537)	3900 (268)
1/2	1/8	S-N8N2	37.3	22.2	19.1	9.7	4.8	7700 (530)	3800 (261)
1/2	1/4	S-N8N4	41.9	22.2	19.1	14.2	7.1	8000 (551)	4000 (275)
1/2	3/8	S-N8N6	41.9	22.2	19.1	14.2	9.7	7800 (537)	3900 (268)
1/2	1/2	S-N8	46.7	22.2	19.1	19.1	11.9	7700 (530)	3800 (261)
3/4	1/8	S-N12N2	40.4	27.0	19.1	9.7	4.8	10000 (689)	5000 (344)
3/4	1/4	S-N12N4	41.9	27.0	19.1	14.2	7.1	8000 (551)	4000 (275)
3/4	3/8	S-N12N6	45.2	27.0	19.1	14.2	9.7	7800 (537)	3900 (268)
3/4	1/2	S-N12N8	46.7	27.0	19.1	19.1	11.9	7700 (530)	3800 (261)
3/4	3/4	S-N12	46.7	27.0	19.1	19.1	15.7	7300 (502)	3600 (248)
1	1/8	S-N16N2	45.2	34.9	23.9	9.7	4.8	10000 (689)	5000 (344)
1	1/4	S-N16N4	49.3	34.9	23.9	14.2	7.1	5300 (365)	2600 (179)
1	3/8	S-N16N6	50.0	34.9	23.9	14.2	9.7	7800 (537)	3900 (268)
1	1/2	S-N16N8	54.1	34.9	23.9	19.1	11.9	7700 (530)	3800 (261)
1	3/4	S-N16N12	54.1	34.9	23.9	19.1	15.7	7300 (502)	3600 (248)
1	1	S-N16	58.9	34.9	23.9	23.9	22.4	5300 (365)	2600 (179)
1 1/4	1	S-N20N16	62.2	44.5	23.9	23.9	22.4	5300 (365)	2600 (179)
1 1/4	1 1/4	S-N20	62.9	44.5	23.9	23.9	28.6	6000 (410)	3000 (200)
1 1/2	1 1/2	S-N24	66.3	50.8	26.2	26.2	34.0	5000 (344)	2500 (172)
2	2	S-N32	77.7	69.9	26.2	26.2	45.0	3900 (268)	1900 (130)

厚壁 NPT 阳螺纹

1/4	1/4	S-N4-10K	35.6	14.3	14.2	14.2	5.8	10000 (689)	/
1/2	1/4	S-N8N4-10K	41.9	22.2	19.1	14.2	5.8	10000 (689)	/
1/2	1/2	S-N8-10K	46.7	22.2	19.1	19.1	9.9	10000 (689)	/

ISO 锥形阳螺纹

P-RT 尺寸	Px-RT 尺寸	基本订购号	尺寸, mm					压力额定值 psig (bar)	
			L	F	B	Bx	E	316 不锈钢, 碳钢	黄铜
1/8	1/8	S-RT2	25.6	11.1	9.7	9.7	4.8	10000 (689)	5000 (344)
1/4	1/4		35.6	14.3	14.2	14.2	7.1	8000 (551)	4000 (275)
3/8	3/8	S-RT6	36.3	17.5	14.2	14.2	9.7	7800 (537)	3900 (268)
1/2	1/2		46.7	22.2	19.1	19.1	11.9	7700 (530)	3800 (261)
3/4	3/4	S-RT12	46.7	27.0	19.1	19.1	15.7	7300 (502)	3600 (248)
1	1		58.9	34.9	23.9	23.9	22.4	5300 (365)	2600 (179)