


阴螺纹活接头




NPT 阴螺纹

P-NPT 尺寸	基本订购号	尺寸, mm					压力额定值 psig (bar) 316 不锈钢,碳钢
		L	F	Fx	B	E	
1/8	UBJ-FN2	46.0	23.8	28.6	10.4	6.8	8400 (578)
1/4	UBJ-FN4	59.4	30.2	34.9	15.0	9.1	6600 (454)
3/8	UBJ-FN6	63.5	33.3	38.1	15.0	13.2	5300 (365)
1/2	UBJ-FN8	68.3	41.3	44.5	19.8	15.7	6000 (410)
3/4	UBJ-FN12	79.2	47.6	54.0	20.6	22.4	4600 (316)
1	UBJ-FN16	90.4	60.3	63.5	25.4	26.2	6800 (468)

ISO 锥形阴螺纹

P-RT 尺寸	基本订购号	尺寸, mm					压力额定值 psig (bar) 316 不锈钢,碳钢
		L	F	Fx	B	E	
1/8	UBJ-FR2	46.0	23.8	28.6	10.4	6.8	8400 (578)
1/4	UBJ-FR4	59.4	30.2	34.9	15.0	9.1	6600 (454)
3/8	UBJ-FR6	63.5	33.3	38.1	15.0	13.2	5300 (365)
1/2	UBJ-FR8	68.3	41.3	44.5	19.8	15.7	6000 (410)
3/4	UBJ-FR12	79.2	47.6	54.0	20.6	22.4	4600 (316)
1	UBJ-FR16	90.4	60.3	63.5	25.4	26.2	6800 (468)

大阴小阳螺纹接头



NPT 阴螺纹

NPT 阳螺纹

P-NPT 尺寸	Px-NPT 尺寸	基本订购号	尺寸, mm					压力额定值 psig (bar)	
			L	F	B	Bx	E	316 不锈钢,碳钢	黄铜
1/8	1/16	S-FN2N1	27.7	14.3	10.4	9.7	3.0	6500 (447)	3200 (220)
1/8	1/8	S-FN2N2	27.9	14.3	10.4	9.7	4.8	6500 (447)	3200 (220)
1/4	1/16	S-FN4N1	30.5	19.1	15.0	9.7	3.0	6600 (454)	3300 (227)
1/4	1/8	S-FN4N2	32.0	19.1	15.0	9.7	4.8	6600 (454)	3300 (227)
1/4	1/4	S-FN4N4	35.6	19.1	15.0	14.2	7.1	6600 (454)	3300 (227)
3/8	1/16	S-FN6N1	31.8	22.2	15.0	9.7	3.0	5300 (365)	2600 (179)
3/8	1/8	S-FN6N2	33.8	22.2	15.0	9.7	4.8	5300 (365)	2600 (179)
3/8	1/4	S-FN6N4	38.1	22.2	15.0	14.2	7.1	5300 (365)	2600 (179)
3/8	3/8	S-FN6N6	38.4	22.2	15.0	14.2	9.7	5300 (365)	2600 (179)
1/2	1/8	S-FN8N2	40.1	27.0	19.8	9.7	4.8	4900 (337)	2400 (165)
1/2	1/4	S-FN8N4	44.7	27.0	19.8	14.2	7.1	4900 (337)	2400 (165)
1/2	3/8	S-FN8N6	44.4	27.0	19.8	14.2	9.6	4900 (337)	2400 (165)
1/2	1/2	S-FN8N8	49.3	27.0	19.8	19.1	11.9	4900 (337)	2400 (165)
3/4	1/8	S-FN12N2	39.6	33.3	20.6	9.7	4.8	4600 (316)	2300 (158)
3/4	1/4	S-FN12N4	47.0	33.3	20.6	14.2	7.1	4600 (316)	2300 (158)
3/4	3/8	S-FN12N6	46.2	33.3	20.6	14.2	9.7	4600 (316)	2300 (158)
3/4	1/2	S-FN12N8	51.3	33.3	20.6	19.1	11.9	4600 (316)	2300 (158)
3/4	3/4	S-FN12N12	51.3	33.3	20.6	19.1	15.7	4600 (316)	2300 (158)
1	1/8	S-FN16N2	46.0	41.3	25.4	9.7	4.8	4400 (303)	2200 (151)
1	1/4	S-FN16N4	49.8	41.3	25.4	14.2	7.1	4400 (303)	2200 (151)
1	3/8	S-FN16N6	50.8	41.3	25.4	14.2	9.7	4400 (303)	2200 (151)
1	1/2	S-FN16N8	54.9	41.3	25.4	19.1	11.9	4400 (303)	2200 (151)
1	3/4	S-FN16N12	55.1	41.3	25.4	19.1	15.7	4400 (303)	2200 (151)
1	1	S-FN16N16	57.9	41.3	25.4	23.9	22.4	4400 (303)	2200 (151)
1 1/4	1	S-FN20N16	62.7	54.0	25.4	23.9	22.4	5000 (344)	2500 (172)

厚壁 NPT 阴螺纹到 NPT 阳螺纹

1/4	1/4	S-FN4-10K	36.3	25.4	15.0	14.2	5.8	10000 (689)	/
1/2	1/2	S-FN8-10K	51.3	38.1	19.8	19.1	9.9	10000 (689)	/
1/2	1/4	S-FN8-FN4-10K	46.0	38.1	19.8	14.2	5.8	10000 (689)	/