





大阴小阳螺纹接头



NPT 阴螺纹

P-NPT 尺寸	Px-RT 尺寸	基本订购号	尺寸, mm					压力额定值 psig (bar)	
			L	F	B	Bx	E	316 不锈钢,碳钢	黄铜
1/8	1/8	S-FN2RT2	27.7	14.3	10.4	9.7	4.8	6500 (447)	3200 (220)
1/4	1/4	S-FN4RT4	36.1	19.1	15.0	14.2	7.1	6600 (454)	3300 (227)
3/8	3/8	S-FN6RT6	38.1	22.2	15.0	14.2	9.7	5300 (365)	2600 (179)
1/2	1/2	S-FN8RT8	49.3	27.0	19.8	19.1	11.9	4900 (337)	2400 (165)
3/4	3/4	S-FN12RT12	51.3	33.3	20.6	19.1	15.7	4600 (316)	2300 (158)
1	1	S-FN16RT16	58.4	41.3	25.4	23.9	22.4	4400 (303)	2200 (151)

ISO 锥形阳螺纹

NPT 阴螺纹

P-NPT 尺寸	Px-RS 尺寸	基本订购号	尺寸, mm						压力额定值 psig (bar)	
			L	F	B	Bx	D	E	316 不锈钢,碳钢	黄铜
1/8	1/8	S-FN2BS2	25.1	14.3	9.9	7.1	13.7	4.1	6500 (447)	3200 (220)
1/4	1/4	S-FN4BS4	33.5	19.1	10.4	11.2	18.0	5.8	6600 (454)	3300 (227)
3/8	3/8	S-FN6BS6	35.8	22.2	15.0	11.2	21.6	7.9	5300 (365)	2600 (179)
1/2	1/2	S-FN8BS8	44.2	27.0	15.0	14.2	25.9	11.9	4900 (337)	2400 (165)
3/4	3/4	S-FN12BS12	48.0	33.3	20.6	15.7	32.0	15.7	4600 (316)	2300 (158)
1	1	S-FN16BS16	53.3	41.3	25.4	18.3	38.9	19.8	4400 (303)	2200 (151)

ISO 平行阳螺纹

ISO 锥形阴螺纹

P-RT 尺寸	Px-RT 尺寸	基本订购号	尺寸, mm					压力额定值 psig (bar)	
			L	F	B	Bx	E	316 不锈钢,碳钢	黄铜
1/8	1/8	S-FR2RT2	27.7	14.3	10.4	9.7	4.8	6500 (447)	3200 (220)
1/4	1/8	S-FR4RT2	32.0	19.1	15.0	9.7	4.8	6600 (454)	3300 (227)
1/4	1/4	S-FR4RT4	36.1	19.1	15.0	14.2	7.1	6600 (454)	3300 (227)
3/8	1/4	S-FR6RT4	38.1	22.2	15.0	14.2	7.1	5300 (365)	2600 (179)
3/8	3/8	S-FR6RT6	38.1	22.2	15.0	14.2	9.7	5300 (365)	2600 (179)
1/2	1/4	S-FR8RT4	44.7	27.0	19.8	14.2	7.1	4900 (337)	2400 (165)
1/2	3/8	S-FR8RT6	44.4	27.0	19.8	14.2	9.7	4900 (337)	2400 (165)
1/2	1/2	S-FR8RT8	49.5	27.0	19.8	19.1	11.9	4900 (337)	2400 (165)
3/4	3/4	S-FR12RT12	51.3	33.3	20.6	19.1	15.7	4600 (316)	2300 (158)
1	1	S-FR16RT16	58.4	41.3	25.4	23.9	22.4	4400 (303)	2200 (151)

ISO 锥形阳螺纹

ISO 锥形阴螺纹

P-RT 尺寸	Px-NPT 尺寸	基本订购号	尺寸, mm					压力额定值 psig (bar)	
			L	F	B	Bx	E	316 不锈钢,碳钢	黄铜
1/8	1/8	S-FR2N2	27.7	14.3	10.4	9.7	4.8	6500 (447)	3200 (220)
1/4	1/4	S-FR4N4	36.3	19.1	15.0	14.2	7.1	6600 (454)	3300 (227)
3/8	3/8	S-FR6N6	38.4	22.2	15.0	14.2	9.6	5300 (365)	2600 (179)
1/2	1/2	S-FR8N8	49.8	27.0	19.8	19.1	11.9	4900 (337)	2400 (165)
3/4	3/4	S-FR12N12	51.3	33.3	20.6	19.1	15.7	4600 (316)	2300 (158)
1	1	S-FR16N16	58.4	41.3	25.4	23.9	22.4	4400 (303)	2200 (151)

NPT 阳螺纹