


六方阴螺纹接头



NPT 阴螺纹

P-NPT 尺寸	Px-NPT 尺寸	基本订购号	尺寸, mm			压力额定值 psig (bar)	
			L	F	E	316 不锈钢, 碳钢	黄铜
1/16	1/16	S-FN1	19.8	11.1	4.8	6700 (460)	3300 (227)
1/8	1/8	S-FN2	20.6	14.3	8.6	6500 (447)	3200 (220)
1/4	1/8	S-FN4FN2	31.0	19.1	8.6	6600 (454)	3300 (227)
1/4	1/4	S-FN4	30.2	19.1	11.4	6600 (454)	3300 (227)
3/8	1/4	S-FN6FN4	35.1	22.2	11.4	5300 (365)	2600 (179)
3/8	3/8	S-FN6	33.3	22.2	15.0	5300 (365)	2600 (179)
1/2	1/8	S-FN8FN2	39.6	27.0	8.6	4900 (337)	2400 (165)
1/2	1/4	S-FN8FN4	44.4	27.0	11.4	4900 (337)	2400 (165)
1/2	3/8	S-FN8FN6	45.2	27.0	15.0	4900 (337)	2400 (165)
1/2	1/2	S-FN8	39.6	27.0	18.5	4900 (337)	2400 (165)
3/4	1/4	S-FN12FN4	46.0	33.3	11.4	4600 (316)	2300 (158)
3/4	1/2	S-FN12FN8	52.3	33.3	18.5	4600 (316)	2300 (158)
3/4	3/4	S-FN12	41.1	33.3	23.9	4600 (316)	2300 (158)
1	1/2	S-FN16FN8	55.6	41.3	18.5	4400 (303)	2200 (151)
1	3/4	S-FN16FN12	57.2	41.3	23.9	4400 (303)	2200 (151)
1	1	S-FN16	50.8	41.3	29.7	4400 (303)	2200 (151)
厚壁 NPT 阴螺纹							
1/4	1/4	S-FN4-10K	30.2	25.4	11.4	10000 (689)	/
1/2	1/2	S-FN8-10K	39.6	38.1	18.5	10000 (689)	/
1/2	1/4	S-FN8FN4-10K	44.4	38.1	11.4	10000 (689)	/

ISO 锥形阴螺纹

P-RT 尺寸	Px-RT 尺寸	基本订购号	尺寸, mm			压力额定值 psig (bar)	
			L	F	E	316 不锈钢, 碳钢	黄铜
1/8	1/8	S-FR2	20.6	14.3	8.4	6500 (447)	3200 (220)
1/4	1/4	S-FR4	30.2	19.1	11.2	6600 (454)	3300 (227)
3/8	1/4	S-FR6FR4	35.1	22.2	11.2	5300 (365)	2600 (179)
3/8	3/8	S-FR6	33.3	22.2	14.7	5300 (365)	2600 (179)
1/2	1/4	S-FR8FR4	44.4	27.0	11.2	4900 (337)	2400 (165)
1/2	3/8	S-FR8FR6	45.2	27.0	14.7	4900 (337)	2400 (165)
1/2	1/2	S-FR8	39.6	27.0	18.3	4900 (337)	2400 (165)