


短管螺纹接头




NPT 阳螺纹

| P-NPT<br>尺寸 | 基本订购号  | 尺寸, mm |      |      | 压力额定值<br>psig (bar) |            |
|-------------|--------|--------|------|------|---------------------|------------|
|             |        | L      | D    | E    | 316 不锈钢, 碳钢         | 黄铜         |
| 1/16        | DS-N1  | 19.1   | 7.9  | 3.0  | 11000 (757)         | 5500 (378) |
| 1/8         | DS-N2  | 19.1   | 10.3 | 4.8  | 10000 (689)         | 5000 (344) |
| 1/4         | DS-N4  | 28.4   | 13.7 | 7.1  | 8000 (551)          | 4000 (275) |
| 3/8         | DS-N6  | 28.4   | 17.1 | 9.6  | 7800 (537)          | 3900 (268) |
| 1/2         | DS-N8  | 38.1   | 21.3 | 11.9 | 7700 (530)          | 3800 (261) |
| 3/4         | DS-N12 | 38.1   | 26.7 | 15.7 | 7300 (502)          | 3600 (248) |
| 1           | DS-N16 | 47.8   | 33.4 | 22.4 | 5300 (365)          | 2600 (179) |

ISO 锥形阳螺纹

| P-RT<br>尺寸 | 基本订购号   | 尺寸, mm |      |      | 压力额定值<br>psig (bar) |            |
|------------|---------|--------|------|------|---------------------|------------|
|            |         | L      | D    | E    | 316 不锈钢, 碳钢         | 黄铜         |
| 1/16       | DS-RT1  | 19.1   | 7.9  | 3.0  | 11000 (757)         | 5500 (378) |
| 1/8        | DS-RT2  | 19.1   | 10.3 | 4.8  | 10000 (689)         | 5000 (344) |
| 1/4        | DS-RT4  | 28.4   | 13.7 | 7.1  | 8000 (551)          | 4000 (275) |
| 3/8        | DS-RT6  | 28.4   | 17.1 | 9.7  | 7800 (537)          | 3900 (268) |
| 1/2        | DS-RT8  | 38.1   | 21.3 | 11.9 | 7700 (530)          | 3800 (261) |
| 3/4        | DS-RT12 | 38.1   | 26.7 | 15.7 | 7300 (502)          | 3600 (248) |
| 1          | DS-RT16 | 47.8   | 33.4 | 22.4 | 5300 (365)          | 2600 (179) |

长管螺纹接头



NPT 阳螺纹

| P-NPT<br>尺寸 | 基本订购号        | 尺寸, mm |      |      | 压力额定值<br>psig (bar) |            |
|-------------|--------------|--------|------|------|---------------------|------------|
|             |              | L      | D    | E    | 316 不锈钢, 碳钢         | 黄铜         |
| 1/8         | DS-N2-38.1   | 38.1   | 10.3 | 4.8  | 10000 (689)         | 5000 (344) |
| 1/8         | DS-N2-50.8   | 50.8   | 10.3 | 4.8  | 10000 (689)         | 5000 (344) |
| 1/8         | DS-N2-63.5   | 63.5   | 10.3 | 4.8  | 10000 (689)         | 5000 (344) |
| 1/8         | DS-N2-76.2   | 76.2   | 10.3 | 4.8  | 10000 (689)         | 5000 (344) |
| 1/4         | DS-N4-38.1   | 38.1   | 13.7 | 7.1  | 8000 (551)          | 4000 (275) |
| 1/4         | DS-N4-50.8   | 50.8   | 13.7 | 7.1  | 8000 (551)          | 4000 (275) |
| 1/4         | DS-N4-63.5   | 63.5   | 13.7 | 7.1  | 8000 (551)          | 4000 (275) |
| 1/4         | DS-N4-76.2   | 76.2   | 13.7 | 7.1  | 8000 (551)          | 4000 (275) |
| 1/4         | DS-N4-101.6  | 101.6  | 13.7 | 7.1  | 8000 (551)          | 4000 (275) |
| 3/8         | DS-N6-38.1   | 38.1   | 17.1 | 9.7  | 7800 (537)          | 3900 (268) |
| 3/8         | DS-N6-50.8   | 50.8   | 17.1 | 9.7  | 7800 (537)          | 3900 (268) |
| 3/8         | DS-N6-63.5   | 63.5   | 17.1 | 9.7  | 7800 (537)          | 3900 (268) |
| 3/8         | DS-N6-76.2   | 76.2   | 17.1 | 9.7  | 7800 (537)          | 3900 (268) |
| 3/8         | DS-N6-101.6  | 101.6  | 17.1 | 9.7  | 7800 (537)          | 3900 (268) |
| 1/2         | DS-N8-50.8   | 50.8   | 21.3 | 11.9 | 7700 (530)          | 3800 (261) |
| 1/2         | DS-N8-76.2   | 76.2   | 21.3 | 11.9 | 7700 (530)          | 3800 (261) |
| 1/2         | DS-N8-101.6  | 101.6  | 21.3 | 11.9 | 7700 (530)          | 3800 (261) |
| 1/2         | DS-N8-152.4  | 152.4  | 21.3 | 11.9 | 7700 (530)          | 3800 (261) |
| 3/4         | DS-N12-50.8  | 50.8   | 26.7 | 15.7 | 7300 (502)          | 3600 (248) |
| 3/4         | DS-N12-76.2  | 76.2   | 26.7 | 15.7 | 7300 (502)          | 3600 (248) |
| 3/4         | DS-N12-101.6 | 101.6  | 26.7 | 15.7 | 7300 (502)          | 3600 (248) |
| 1           | DS-N16-76.2  | 76.2   | 33.4 | 22.4 | 5300 (365)          | 2600 (179) |
| 1           | DS-N16-101.6 | 101.6  | 33.4 | 22.4 | 5300 (365)          | 2600 (179) |