


阴螺纹弯头



NPT 阴螺纹

P-NPT 尺寸	Px-NPT 尺寸	基本订购号	尺寸, mm						压力额定值 psig (bar)	
			L	F	B	E	Lx	Bx	316 不锈钢, 碳钢	黄铜
1/16	1/16	L-FN1	21.8	11.1	9.9	4.8	21.8	9.9	6700 (460)	3300 (227)
1/8	1/16	L-FN2FN1	26.4	12.7	10.4	4.8	26.4	9.9	6200 (427)	3100 (213)
1/8	1/8	L-FN2	26.4	12.7	10.4	8.6	26.4	10.4	6200 (427)	3100 (213)
1/4	1/8	L-FN4FN2	29.7	17.5	15.0	7.1	29.7	10.4	7200 (496)	3600 (248)
1/4	1/4	L-FN4	29.7	17.5	15.0	11.4	29.7	15.0	7200 (496)	3600 (248)
3/8	3/8	L-FN6	36.1	20.6	15.0	15.0	36.1	15.0	5600 (385)	2800 (192)
1/2	1/2	L-FN8	39.6	25.4	19.8	18.5	39.6	19.8	5600 (385)	2800 (192)
3/4	3/4	L-FN12	48.8	31.8	20.6	23.9	48.8	20.6	5100 (351)	2500 (172)
1	1	L-FN16	48.5	42.9	25.4	29.7	48.5	25.4	6400 (440)	3200 (220)
1 1/4	1 1/4	L-FN20	59.8	50.8	25.4	27.7	50.8	25.4	3100 (213)	1600 (110)
1 1/2	1 1/2	L-FN24	65.0	63.5	27.7	34.0	52.8	27.7	5100 (351)	2500 (172)

厚壁 NPT 阴螺纹

1/4	1/4	L-FN4-10K	39.6	25.4	15.0	11.4	29.7	15.0	10000 (689)	/
1/2	1/2	L-FN8-10K	50.0	42.9	19.8	18.5	39.6	19.8	10000 (689)	/

ISO 锥形阴螺纹

P-RT 尺寸	Px-RT 尺寸	基本订购号	尺寸, mm						压力额定值 psig (bar)	
			L	F	B	E	Lx	Bx	316 不锈钢, 碳钢	黄铜
1/16	1/16	L-FR1	21.8	11.1	9.9	4.8	21.6	9.9	6700 (460)	3300 (227)
1/8	1/16	L-FR2FR1	16.8	12.7	10.4	4.8	16.8	9.9	6200 (427)	3100 (213)
1/8	1/8	L-FR2	26.4	12.7	10.4	7.1	26.4	10.4	6200 (427)	3100 (213)
1/4	1/8	L-FR4FR2	29.7	17.5	15.0	7.1	29.7	10.4	7200 (496)	3600 (248)
1/4	1/4	L-FR4	29.7	17.5	15.0	10.4	29.7	15.0	7200 (496)	3600 (248)
3/8	3/8	L-FR6	36.1	20.6	15.0	12.7	36.1	15.0	5600 (385)	2800 (192)
1/2	1/2	L-FR8	39.6	25.4	19.8	15.7	39.6	19.8	5600 (385)	2800 (192)
3/4	3/4	L-FR12	48.8	31.8	20.6	22.4	48.8	20.6	5100 (351)	2500 (172)
1	1	L-FR16	48.5	42.9	25.4	22.4	48.5	25.4	6400 (440)	3200 (220)
1 1/4	1 1/4	L-FR20	59.8	50.8	25.4	27.7	50.8	25.4	3100 (213)	1600 (110)
1 1/2	1 1/2	L-FR24	65.0	63.5	27.7	34.0	52.8	27.7	5100 (351)	2500 (172)