


阴螺纹三通



NPT 阴螺纹

P-NPT 尺寸	基本订购号	尺寸, mm				压力额定值 psig (bar)	
		L	F	E	B	316 不锈钢, 碳钢	黄铜
1/16	T-FN1	21.8	11.1	4.8	9.9	6700 (460)	3300 (227)
1/8	T-FN2	26.4	12.7	8.6	10.4	6200 (427)	3100 (213)
1/4	T-FN4	29.7	17.5	11.4	15.0	7200 (496)	3600 (248)
3/8	T-FN6	36.1	20.6	15.0	15.0	5600 (385)	2800 (192)
1/2	T-FN8	39.6	25.4	18.5	19.8	5600 (385)	2800 (192)
3/4	T-FN12	48.8	31.8	23.9	20.6	5100 (351)	2500 (172)
1	T-FN16	48.5	42.9	29.7	25.4	6400 (440)	3200 (220)
1 1/4	T-FN20	59.8	50.8	37.2	25.4	3100 (213)	1600 (110)
1 1/2	T-FN24	65.0	63.5	43.3	27.7	5100 (351)	2500 (172)
厚壁 NPT 阴螺纹							
1/4	T-FN4-10K	39.6	25.4	11.4	15.0	10000 (689)	/
1/2	T-FN8-10K	50.0	27.0	18.5	19.8	10000 (689)	/

ISO 锥形阴螺纹

P-RT 尺寸	基本订购号	尺寸, mm				压力额定值 psig (bar)	
		L	F	E	B	316 不锈钢, 碳钢	黄铜
1/16	T-FR1	21.8	11.1	4.8	9.9	6700 (460)	3300 (227)
1/8	T-FR2	26.4	12.7	8.6	10.4	6200 (427)	3100 (213)
1/4	T-FR4	29.7	17.5	11.2	15.0	7200 (496)	3600 (248)
3/8	T-FR6	36.1	20.6	14.7	15.0	5600 (385)	2800 (192)
1/2	T-FR8	39.6	25.4	18.3	19.8	5600 (385)	2800 (192)
3/4	T-FR12	48.8	31.8	23.9	20.6	5100 (351)	2500 (172)
1	T-FR16	48.5	42.9	29.7	25.4	6400 (440)	3200 (220)
1 1/4	T-FR20	59.8	50.8	37.2	25.4	3100 (213)	1600 (110)
1 1/2	T-FR24	65.0	63.5	43.3	27.7	5100 (351)	2500 (172)