


支管阴螺纹三通




NPT 螺纹

P-NPT 尺寸 基本订购号	尺寸, mm						压力额定值 psig (bar)	
	L	F	E	B	Lx	Bx	316 不锈钢, 碳钢	黄铜
1/16 T-N1N1FN1	18.3	11.1	3.0	9.7	21.8	9.9	9200 (633)	4600 (316)
1/8 T-N2N2FN2	22.1	12.7	4.8	9.7	26.4	10.4	6200 (427)	3100 (213)
1/4 T-N4N4FN4	29.7	17.5	7.1	14.2	29.7	15.0	7200 (496)	3600 (248)
3/8 T-N6N6FN6	32.0	20.6	9.7	14.2	36.1	15.0	5600 (385)	2800 (192)
1/2 T-N8N8FN8	39.6	25.4	11.9	19.1	39.6	19.8	5600 (385)	2800 (192)
3/4 T-N12N12FN12	42.4	31.8	15.7	19.1	48.8	20.6	5100 (351)	2500 (172)
1 T-N16N16FN16	49.3	42.9	22.4	23.9	48.5	25.4	5300 (365)	2600 (179)

ISO 锥形螺纹

P-RT 尺寸 基本订购号	尺寸, mm						压力额定值 psig (bar)	
	L	F	E	B	Lx	Bx	316 不锈钢, 碳钢	黄铜
1/16 T-RT1RT1FR1	18.3	11.1	3.0	9.7	21.8	9.9	9200 (633)	4600 (316)
1/8 T-RT2RT2FR2	22.1	12.7	4.8	9.7	26.4	10.4	6200 (427)	3100 (213)
1/4 T-RT4RT4FR4	29.7	17.5	7.1	14.2	29.7	15.0	7200 (496)	3600 (248)
3/8 T-RT6RT6FR6	32.0	20.6	9.7	14.2	36.1	15.0	5600 (385)	2800 (192)
1/2 T-RT8RT8FR8	39.6	25.4	11.9	19.1	39.6	19.8	5600 (385)	2800 (192)
3/4 T-RT12RT12FR12	42.4	31.8	15.7	19.1	48.8	20.6	5100 (351)	2500 (172)
1 T-RT16RT16FR16	49.3	42.9	22.4	23.9	48.5	25.4	5300 (365)	2600 (179)

主管阴螺纹三通



NPT 螺纹

P-NPT 尺寸 基本订购号	尺寸, mm						压力额定值 psig (bar)	
	L	F	E	B	Lx	Bx	316 不锈钢, 碳钢	黄铜
1/16 T-FN1N1N1	21.8	11.1	3.0	9.9	18.3	9.7	9200 (633)	4600 (316)
1/8 T-FN2N2N2	26.4	12.7	4.8	10.4	22.1	9.7	6200 (427)	3100 (213)
1/4 T-FN4N4N4	29.7	17.5	7.1	15.0	29.7	14.2	7200 (496)	3600 (248)
3/8 T-FN6N6N6	36.1	20.6	9.7	15.0	32.0	14.2	5600 (385)	2800 (192)
1/2 T-FN8N8N8	39.6	25.4	11.9	19.8	39.6	19.1	5600 (385)	2800 (192)
3/4 T-FN12N12N12	48.8	31.8	15.7	20.6	42.4	19.1	5100 (351)	2500 (172)
1 T-FN16N16N16	48.5	42.9	22.4	25.4	49.3	23.9	5300 (365)	2600 (179)

ISO 锥形螺纹

P-RT 尺寸 基本订购号	尺寸, mm						压力额定值 psig (bar)	
	L	F	E	B	Lx	Bx	316 不锈钢, 碳钢	黄铜
1/16 T-FR1RT1RT1	21.8	11.1	3.0	9.9	18.3	9.7	9200 (633)	4600 (316)
1/8 T-FR2RT2RT2	26.4	12.7	4.8	10.4	22.1	9.7	6200 (427)	3100 (213)
1/4 T-FR4RT4RT4	29.7	17.5	7.1	15.0	29.7	14.2	7200 (496)	3600 (248)
3/8 T-FR6RT6RT6	36.1	20.6	9.7	15.0	32.0	14.2	5600 (385)	2800 (192)
1/2 T-FR8RT8RT8	39.6	25.4	11.9	19.8	39.6	19.1	5600 (385)	2800 (192)
3/4 T-FR12RT12RT12	48.8	31.8	15.7	20.6	42.4	19.1	5100 (351)	2500 (172)
1 T-FR16RT16RT16	48.5	42.9	22.4	25.4	49.3	23.9	5300 (365)	2600 (179)